



20-40' SCOOP TYPE BOMBCART

New 2009 heavy duty container chassis with corners for stevedoring and local port transport of 2 x 20ft, one 20ft, or one 40ft ISO shipping containers. Meets all AAR, FMVSS, ISO, ANSI, DOT, ABS, SAE and TTMA specifications at the time of manufacture and applicable to operation in the United States.

Overall Length:	42'
Overall Width:	106"
King Pin Location:	24"
Coupler Height:	48"
Capacity:	106,000 lb
Main Rails:	Two hot rolled structural steel, ASTM-A572 Grade 50 "I" beams. Wide flange 21" in depth 57 lbs/ft.
Container Guides:	Front, rear and side sloped gathering guides plates
Landing Gear:	Non-telescoping 3/8" wall tubing; height adjustable via bolts; 10" x 10" sand shoes
Suspension:	Hutch 900 Single Point suspension rated at 60,000 lbs
Axles:	Two Axles of 5" round and 25,000 lb beam capacity each; 16.5x 7-inch Q brakes; automatic type slack adjusters
Tires / Wheels:	11R22.5 tires on 10-hole disc wheels
Brake System:	30/30 Spring brake chambers, No ABS
Twistlocks:	Optional
Electrical/ Lights:	12 Volt with plug type connectors, 7-way plug, sealed wire harnesses and lights
Paint:	Commercial sandblast, primer, and high quality paint system
Other:	Conspicuity Tape, Bumper, 24x30 Mud Flaps

Call Chassis King at 727-585-1500 for more info !