



20' FLUSHBACK CHASSIS

New container chassis designed for repeated use in stevedoring and transporting of a 20 ft ISO type cargo container. Meets all AAR, FMVSS, ISO, ANSI, DOT, ABS, SAE and TTMA specifications at the time of manufacture and applicable to operation in the United States.

Overall Length:	23'-6"
Overall Width:	96"
King Pin Location:	18" from front of chassis
Coupler Height:	48"
Tare Weight:	6500 lbs
Main Rails:	Two hot rolled structural steel, ASTM-A572 Grade 50 "I" beams. Wide flange 12" in depth 19 lbs/ft.
Landing Gear:	Two speed, 50,000 lb. lift capacity, and 170,000 lb. static load capacity. Low profile 10" x 10" sand shoes.
Suspension:	Hutch with Three Leaf Springs (11,000 lb capacity each)
Axles:	Two axles of 5" round and 22,500 lb beam capacity each; 16.5x7-inch Q brakes; automatic type slack adjusters
Brake System:	Meritor Wabco 2S/1M Anti-lock Braking System; 30/30 Spring brake chambers
Tires / Wheels	11R22.5 tires on 10 hole disc wheels
Electrical:	12 Volt with plug type connectors, 7-way plug, sealed wire harnesses and lights
Twist Locks:	Cast steel to engage ISO corner castings
Paint:	Commercial sandblast, primer, and high quality paint system
Other:	Conspicuity Tape, Bumper, 24x30 Mud Flaps

Call Chassis King at 727-585-1500 for more info !