



20' SLIDER CHASSIS

Container chassis designed for repeated use in stevedoring and transporting of a 20 ft ISO type cargo container. Meets all AAR, FMVSS, ISO, ANSI, DOT, ABS, SAE and TTMA specifications at the time of manufacture and applicable to operation in the United States.

Ride Like a King

Overall Length:	23'-6" Retracted ; 27'-6" Extended
Overall Width:	96"
King Pin Location:	18" from front of chassis
Coupler Height:	48"
Tare Weight:	6600 lbs
Main Rails:	Two hot rolled structural steel, ASTM-A572 Grade 50 "I" beams. Wide flange 12" in depth 19 lbs/ft.
Landing Gear:	Two-speed mechanism and square leg tubing with 10" x 10" low profile sand shoes
Suspension:	Hutch with Three Leaf Springs (11,000 lb capacity each)
Axles:	Two axles of 5" round and 22,500 lb beam capacity each; 16.5x 7-inch Q brakes; automatic type slack adjusters
Brake System:	Meritor Wabco 2S/1M Anti-lock Braking System; 30/30 Spring brake chambers
Tires / Wheels	11R22.5 tires on 10-hole disc wheels
Electrical:	12 Volt with plug type connectors, 7-way plug, sealed wire harnesses and lights
Twist Locks:	Cast steel to engage ISO corner castings
Paint:	Commercial sandblast, primer, and high quality paint system
Other:	Conspicuity Tape, Bumper, 24x30 Mud Flaps

Call Chassis King at 727-585-1500 for more info !