



43' SPREAD AXLE TANK CHASSIS

New drop frame container chassis designed for repeated use in stevedoring and transporting of a 20 ft ISO type cargo container. Meets all AAR, FMVSS, ISO, ANSI, DOT, ABS, SAE and TTMA specifications at the time of manufacture and applicable to operation in the United States.

Ride Like a King

<i>Overall Length:</i>	<i>43'-3"</i>
<i>Overall Width:</i>	<i>96"</i>
<i>King Pin Location:</i>	<i>15"</i>
<i>Frame Height:</i>	<i>41.5" at container</i>
<i>Axle Centers:</i>	<i>109"</i>
<i>Tare Weight:</i>	<i>7400 lbs</i>
<i>Main Rails:</i>	<i>Fabricated high strength steel main beams</i>
<i>Landing Gear:</i>	<i>Two speed, 50,000 lb. lift capacity, and 140,000 lb. static load capacity. Low profile 10" x 10" sand shoes.</i>
<i>Suspension:</i>	<i>Hutch with Two Leaf Springs</i>
<i>Axles:</i>	<i>Two Meritor Axles of 5" round and 22,500 lb beam capacity each; 16.5x 7-inch Q brakes; automatic type slack adjusters</i>
<i>Brake System:</i>	<i>Meritor Wabco 2S/1M Anti-lock Braking System; 30/30 Spring brake chambers</i>
<i>Tires / Wheels</i>	<i>255/70R22.5 tires on 10-hole disc wheels</i>
<i>Electrical:</i>	<i>12 Volt with plug type connectors, 7-way plug, sealed wire harnesses and lights</i>
<i>Twist Locks</i>	<i>Cast steel to engage ISO corner castings</i>
<i>Paint:</i>	<i>Commercial sandblast, primer, and high quality paint system</i>
<i>Other:</i>	<i>Rear Deck, Conspicuity Tape, 24x30 Mud Flaps, Fenders</i>

Call Chassis King at 727-585-1500 for more info !



43' TANK CHASSIS

Typical Layout of Spread Axle

